CLAIMS

What is claimed is:

1 1.   A method for capturing illegal and undesired behavior for network components and

2 for interactions between components comprising:

3   specifying one or more states and state transitions for one or more components or

4 interactions between two or more components, wherein specifying includes specifying at

5 least one composite state transition; and

6   if a said state or state transition occurs, generating a notification corresponding to the

7 specified state or state transition.

1 2.   The method recited in claim 1, wherein said states are specified based on thresholds.

1 3.   The method recited in claim 1, wherein the notification is an event.

1 4.   The method recited in claim 1, wherein a state or state transition is a state or state

2 transition of a component, and wherein the step of generating the notification comprises

3 generating the notification by the component.

1

1 5.   The method recited in claim 1, wherein if the state or state transition relates to an

2 interaction between components, and wherein the notification is generated by at least one of

3 the components involved in the interaction between the components.

1 6.   The method recited in claim 1, further comprising the step of:

2   reporting the notification to a network management system.

-28-

1   7.   The method recited in claim 1, further comprising the step of:

2   detecting whether a state or state transition has occurred; and

3   wherein if said step of detecting detects that a state or state transition has occurred,

4   said notification is generated in response to said step of detecting.

1   8.   The method recited in claim 7, wherein, the step of detecting is performed by an

2   agent.

1   9.   The method recited in claim 8, wherein the agent is a dedicated agent.

1   10.   The method recited in claim 1, further comprising the step of polling said components

2   to determine whether a state or state transition has occurred.

1   11.   The method recited in claim 1, wherein the step of specifying one or more states and

2   state transitions comprises specifying illegal states.

1   12.   The method recited in claim 1, wherein the step of specifying one or more states and

2   state transitions comprises specifying undesired states.

1   13.   The method recited in claim 1, wherein the step of specifying one or more states and

2   state transitions comprises specifying illegal states and undesired states.

1 14. The method recited in claim 6, wherein detecting whether a state or state transition

2 has occurred comprises determining whether a component or component interaction has

3 entered an illegal or undesired state.

1 15. The method recited in claim 11 wherein an authorization violation and an

2 authentication forgery are defined as illegal states.

1 16. The method recited in claim 12, wherein a nongracefully QoS degradation is defined

2 as an undesired state.

1 17. The method recited in claim 1, further comprising the step of examining multiple

2 notifications to deduce trends regarding the network.

1

1 18. The method recited in claim 17, wherein the step of examining multiple notifications

2 comprises examining notifications for stable-behavior in a threshold value.

1 19. The method recited in claim 17, wherein the step of examining multiple notifications

2 comprises examining notifications for increases or decreases in a threshold value.

1 20. A system for capturing illegal and undesired behavior for network components and

2 for interactions between components, the system comprising:

3   one or more network components configured to spontaneously generate notifications

4 upon the occurrence of specified states and state transitions, including one or more

5 composite state transitions; and

-30-

6   a network management system configured to receive said spontaneously generated

7   notifications.

1   21.   The system of claim 20, further comprising:

2   an agent configured to detect the generation of notifications by the network

3   components, and configured to report detected notifications to said network management

4   system.

1   22.   The system of claim 20, further comprising:

2   a state table configured to store said specified states and state transitions, including

3   composite state transitions.

1   23.   The system of claim 21, wherein the state table is in a network management system.

1   24.   The system of claim 21, wherein the state table is in a network component.

1   25.   The system of claim 22, wherein the agent is further configured to examine one or

2   more conditions of one or more network components and to query the state table to

3   determine whether the one or more conditions represents an illegal or undesired state.

1   26.   The system of claim 22, wherein the agent is further configured to examine one or

2   more transitions relating to one or more network components and to query the state table to

3   determine whether the one or more transitions represents an illegal or undesired transition.

1 27.   A system for capturing illegal and undesired behavior for network components and

2 for interactions between components comprising:

3   one or more network components;

4   an agent configured to examine said network components to determine whether

5 specified states or state transitions, including composite state transitions, have occurred,

6 wherein the agent is configured to generate notifications upon a determination that a

7 specified state or state transition has occurred, and wherein the agent is configured to report

8 detected notifications to said network management system; and

9   a network management system configured to receive reports of said generated

10 notifications.

1 28.   The system of claim 27, further comprising:

2   a state log configured to store said specified states and state transitions, including

3 composite state transitions.

1 29.   A computer-readable medium carrying one or more sequences of instructions for

2 capturing illegal and undesired behavior for network components and for interactions

3 between components, which instructions, when executed by one or more processors, cause

4 the one or more processors to carry out the steps of:

5   specifying one or more states and state transitions for one or more components or

6 interactions between two or more components, wherein specifying includes specifying at

7 least one composite state transition; and

8   if a said state or state transition occurs, generating a notification corresponding to the

9 specified state or state transition.

50325-0780 (Seq. No. 7182)

1 30.   A computer-readable medium as recited in Claim 29, wherein said states are specified

2 based on thresholds.

1 31.   A computer-readable medium as recited in Claim 29, wherein said notifications are

2 events.

1 32.   A computer-readable medium as recited in Claim 29, wherein a state or state

2 transition is a state or state transition of a component, and wherein the step of generating a

3 notification comprises generating the notification by the component.

1

1 33.   A computer-readable medium as recited in Claim 29, wherein if the state or state

2 transition relates to an interaction between components, and wherein the notification is

3 generated by at least one of the components involved in the interaction between the

4 components.

1 34.   A computer-readable medium as recited in Claim 29, wherein the instructions for

2 carrying out the step of creating and storing first information further comprise instructions

3 for carrying out the step of:

4   reporting the notification to a network management system.

1 35.   A computer-readable medium as recited in Claim 29, wherein the instructions for

2 carrying out the step of creating and storing first information further comprise instructions

3 for carrying out the steps of:

4   detecting whether a state or state transition has occurred; and

5   wherein if said step of detecting detects that a state or state transition has occurred,

6   said notification is generated in response to said step of detecting.

1   36.   A computer-readable medium as recited in Claim 35, wherein the step of detecting is

2   performed by an agent.

1   37.   A computer-readable medium as recited in Claim 36, wherein the agent is a dedicated

2   agent.

1   38.   A computer-readable medium as recited in Claim 29, wherein the instructions for

2   carrying out the step of creating and storing first information further comprise instructions

3   for carrying out the step of:

4   polling said components to determine whether a state or state transition has occurred.

1   39.   A computer-readable medium as recited in Claim 29, wherein the step of specifying

2   one or more states and state transitions comprises specifying illegal states.

1   40.   A computer-readable medium as recited in Claim 29, wherein the step of specifying

2   one or more states and state transitions comprises specifying undesired states.

1   41.   A computer-readable medium as recited in Claim 29, wherein the step of specifying

2   one or more states and state transitions comprises specifying illegal states and undesired

3   states.

1 42.   A computer-readable medium as recited in Claim 35, wherein detecting whether a

2 state or state transition has occurred comprises determining whether a component or

3 component interaction has entered an illegal or undesired state.

1 43.   A computer-readable medium as recited in Claim 39, wherein an authorization

2 violation and an authentication forgery are defined as illegal states.

1 44.   A computer-readable medium as recited in Claim 40, wherein a nongracefully QoS

2 degradation is defined as an undesired state.

1 45.   A computer-readable medium as recited in Claim 29, wherein the instructions for

2 carrying out the step of creating and storing first information further comprise instructions

3 for carrying out the step of examining multiple notifications to deduce trends regarding the

4 network.

1

1 46.   A computer-readable medium as recited in Claim 45, wherein the step of examining

2 multiple notifications comprises examining notifications for stable-behavior in a threshold

3 value.

1 47.   A computer-readable medium as recited in Claim 45, wherein the step of examining

2 multiple notifications comprises examining notifications for increases or decreases in a

3 threshold value.